

INTERNATIONAL SEALSKIN™
EXTRA FLEXIBLE LIQUID-TIGHT
METALLIC CONDUIT
 (NON-UL CONTRACTOR GRADE. TYPE EFLT)

FEATURES:

- Extra flexible for easy use
- Corrosion resistant steel core for lasting mechanical protection
- Durable, abrasion resistant PVC jacket won't wrinkle or shrink from cut ends
- Complete protection against most liquids and moisture vapor
- Resists sunlight, heat, oil and chemical degradation
- RoHS WEEE compliant
- Smooth interior for easy wire pull-thru
- Easily cut to length on the job
- Accepts standard liquid-tight connectors
- Delivers long-lasting wiring protection where listed products are not required
- Generally applicable temperature range:
 -20° C to +60° C (- 5° F to +140° F)

USES:

International Sealskin™ gives lasting wiring protection on machine tools, portable tools, presses, welders, pumps, blowers, grinders, conveyors, heating equipment and automated lines for forging, plating, molding, blasting, rolling, die casting, processing, extruding, etc.

SPECIFICATIONS:

Trade Size And Catalog Number	Acceptable Internal Diameter		Acceptable External Diameter		Bending Radius in inches	Approx. Weight of 100 Ft	Feet Per Standard Pkg.
	Min.	Max.	Min.	Max.			
EFLT-3/8*	0.484	0.504	0.690	0.710	1-1/2	19	100
EFLT-1/2*	0.622	0.642	0.820	0.840	2	24	100
EFLT-3/4*	0.820	0.840	1.030	1.050	2-3/4	32	100
EFLT-1*	1.041	1.066	1.290	1.315	5	55	100
EFLT-1-1/4*	1.380	1.410	1.630	1.660	6	67	100
EFLT-1-1/2*	1.575	1.600	1.865	1.900	7	92	50
EFLT-2*	2.020	2.045	2.340	2.375	9	120	50
EFLT-2-1/2	2.480	2.505	2.840	2.875	11	150	50
EFLT-3	3.070	3.100	3.460	3.500	15- 1/2	260	25
EFLT-3-1/2	3.500	3.540	3.960	4.000	18	310	25
EFLT-4	4.000	4.040	4.460	4.500	22	360	25

*Also available on reels, and special packaging - consult factory

*Standard length tolerance on packaging +/- 2%



INTERNATIONAL
METAL HOSE COMPANY

QUALITY MATERIALS • QUALITY MANUFACTURING
 QUALITY PERFORMANCE

520 Goodrich Road – Bellevue, OH 44811-0149 – Phone: 419.483.7690
 Fax: 419.483.8225 – Toll Free: 800.458.6855 – www.metalhose.com

