

# INTERNATIONAL SEALSKIN™ COMPUTER BLUE LIQUID-TIGHT EXTRA FLEXIBLE METALLIC CONDUIT

(UL LISTED. CSA CERTIFIED. TYPE CBLT)

CBLT



## FEATURES:

- Galvanized steel core for lasting mechanical protection
- Durable, abrasion resistant PVC jacket won't wrinkle or shrink from cut ends
- Complete protection against most liquids and moisture vapor
- Resists sunlight, heat, oil and chemical degradation: Rated: -20° C to +60° C (-5° F to +140° F)
- Extra flexible for extra easy use
- The armor is approved as an equipment ground in sizes 3/8" through 1-1/4"
- Exceptional crush proof qualities
- RoHS WEEE compliant
- Complies with UL standard 360, File number E34028, CSA C22.2 File number LL21229-4, NEC Article 350
- Packaged in handy payout carton
- Accepts standard liquid-tight connectors
- Delivers long-lasting wiring protection
- Bright blue cover easily identifies computer wiring
- Copper bond wire in 3/8" - 1 1/4"
- Smooth interior for easy wire pull-thru

## NEC Articles:

- Article 250.118 Equipment Grounding
- Article 300.22 Air Plenum
- Article 350 Liquidtight Flexible Metal Conduit
- Article 501.10, Class I, Div. 2, Classes II and III
- Article 502.10, Class II, Div. 1 & 2
- Article 503.10, Class III, Div. 1&2
- Article 511.7, Above Class I Locations
- Article 620.21 Elevators, Escalators and Platform Lifts
- Article 645.5 Information Technology Equipment
- Article 680.42 Pools, Hot Tubs and Fountains
- Article 695.6 Electrical Fire Pump

## USES:

International Sealskin™ Computer Blue gives lasting wiring protection throughout a broad range of computer environments. Also suitable for equipment where rugged and extremely flexible conduit is needed for connections between moving members and stationary parts.

## SPECIFICATIONS:

Trade Size And Catalog Number	Acceptable Internal Diameter		Acceptable External Diameter		Bending Radius in Inches	Approx. Weight of 100 Ft.	Feet Per Standard Pkg.
	Min.	Max.	Min.	Max.			
CBLT-3/8*	0.484	0.504	0.690	0.710	2	26	100
CBLT-1/2*	0.622	0.642	0.820	0.840	3-1/4	32	100
CBLT-3/4*	0.820	0.840	1.030	1.050	4-1/4	42	100
CBLT-1*	1.041	1.066	1.290	1.315	6-1/2	63	100
CBLT-1-1/4*	1.380	1.410	1.630	1.660	8	90	50
CBLT-1-1/2*	1.575	1.600	1.865	1.900	9	116	50
CBLT-2*	2.020	2.045	2.340	2.375	11	150	50
CBLT-2-1/2†	2.480	2.505	2.840	2.875	14	225	50
CBLT-3†	3.070	3.100	3.460	3.500	17-1/2	260	25
CBLT-3-1/2†	3.500	3.540	3.960	4.000	20	310	25
CBLT-4†	4.000	4.040	4.460	4.500	24	360	25

\*Also available on reels. †Special order sizes. Consult factory for lead time.

\*Standard length tolerance on packaging +/- 2%



**INTERNATIONAL**  
METAL HOSE COMPANY

**QUALITY MATERIALS • QUALITY MANUFACTURING  
QUALITY PERFORMANCE**

520 Goodrich Road – Bellevue, OH 44811-0149 – Phone: 419.483.7690  
Fax: 419.483.8225 – Toll Free: 800.458.6855 – www.metallhose.com

