

**INTERNATIONAL SEALSKIN™
HI-LOW TEMPERATURE
LIQUID-TIGHT FLEXIBLE
METALLIC CONDUIT
(TYPE HLT)**

HLT



FEATURES:

- Stabilized polyvinyl chloride compound jacket
- Maintains flexibility through exceptionally low or high temperatures
- Temperature range: -40° C to +105° C (-40° F to +220° F)
- Smooth interior for easy wire pull-thru
- Sunlight resistant
- Complete protection against most liquids and moisture vapor
- Connectors available from leading manufacturers
- Superior protection for circuits located in hostile environments
- Exceeds ASTM standards for temperature
- RoHS WEEE compliant

USES:

International Sealskin™ HLT Flexible Metallic Conduit is especially suitable for wiring application inside cold storage areas and is suitable for wiring most types of industrial equipment, which are subjected to moisture from coolant, and other wiring hazards.

SPECIFICATIONS:

Trade Size And Catalog Number	Acceptable Internal Diameter Min. Max.	Acceptable External Diameter Min. Max.	Bending Radius in Inches	Approx. Weight of 100 Ft.	Feet Per Standard Pkg.
HLT-3/8*	0.484 0.504	0.690 0.710	2	19	100
HLT-1/2*	0.622 0.642	0.820 0.840	2-1/2	24	100
HLT-3/4*	0.820 0.840	1.030 1.050	3	32	100
HLT-1*	1.041 1.066	1.290 1.315	5-1/2	55	100
HLT-1-1/4*	1.380 1.410	1.630 1.660	6-1/2	67	100
HLT-1-1/2*	1.575 1.600	1.865 1.900	7-1/2	92	50
HLT-2*	2.020 2.045	2.340 2.375	9-1/2	120	50
HLT-2-1/2	2.480 2.505	2.840 2.875	11-1/2	150	50
HLT-3	3.070 3.100	3.460 3.500	16	260	25
HLT-3-1/2	3.500 3.540	3.960 4.000	19	310	25
HLT-4	4.000 4.040	4.460 4.500	23	360	25

*Also available on reels. Available in black and other colors on request – consult factory.

*Standard length tolerance on packaging +/- 2%



**INTERNATIONAL
METAL HOSE COMPANY**

**QUALITY MATERIALS • QUALITY MANUFACTURING
QUALITY PERFORMANCE**

520 Goodrich Road – Bellevue, OH 44811-0149 – Phone: 419.483.7690
Fax: 419.483.8225 – Toll Free: 800.458.6855 – www.metallhose.com

