

**INTERNATIONAL SEALSKIN™
OIL RESISTANT LIQUID-TIGHT
FLEXIBLE METALLIC CONDUIT
(TYPE OR)**

OR



FEATURES:

- Stabilized polyvinyl chloride compound jacket
- Temperature range: -40° C to +105° C (-40° F to +220° F)
60° C (140° F) wet,
70° C (158° F) oil resistant
- Highly resistant to most oil and chemical degradation
- Exceeds ASTM standards for oil resistance
- Smooth interior for easy wire pull-thru
- Complete protection against most liquids and moisture vapor
- Connectors available from leading manufacturers
- Superior protection for circuits located in hostile environments
- RoHS WEEE compliant

USES:

International Sealskin™ OR Flexible Metallic Conduit is especially suitable for wiring machine tools, hydraulic presses and other types of industrial equipment, which are subjected to moisture from coolant, oils and fluids.

SPECIFICATIONS:

Trade Size And Catalog Number	Acceptable Internal Diameter		Acceptable External Diameter		Bending Radius in Inches	Approx. Weight of 100 Ft.	Feet Per Standard Pkg.
	Min.	Max.	Min.	Max.			
OR-3/8*	0.484	0.504	0.690	0.710	2	19	100
OR-1/2*	0.622	0.642	0.820	0.840	2-1/2	24	100
OR-3/4*	0.820	0.840	1.030	1.050	3	32	100
OR-1*	1.041	1.066	1.290	1.315	5-1/2	55	100
OR-1-1/4*	1.380	1.410	1.630	1.660	6-1/2	67	100
OR-1-1/2*	1.575	1.600	1.865	1.900	7-1/2	92	50
OR-2*	2.020	2.045	2.340	2.375	9-1/2	120	50
OR-2-1/2	2.480	2.505	2.840	2.875	11-1/2	150	50
OR-3	3.070	3.100	3.460	3.500	16	260	25
OR-3-1/2	3.500	3.540	3.960	4.000	19	310	25
OR-4	4.000	4.040	4.460	4.500	23	360	25

*Also available on reels. Available in grey only.

*Standard length tolerance on packaging +/- 2%



**INTERNATIONAL
METAL HOSE COMPANY**

**QUALITY MATERIALS • QUALITY MANUFACTURING
QUALITY PERFORMANCE**

520 Goodrich Road – Bellevue, OH 44811-0149 – Phone: 419.483.7690
Fax: 419.483.8225 – Toll Free: 800.458.6855 – www.metallhose.com

