



# INTERNATIONAL APPLIANCE FLEX ALUMINUM CONDUIT

(UL RECOGNIZED. COMPONENT GRADE. TYPE AFA)

## FEATURES:

- Extra flexible aluminum construction
- Tempered primary aluminum alloy for maximum strength
- Superior corrosion resistance
- Smooth interior for easy wire pull-thru
- Built-in flexibility for simplified positioning
- Exceptional flexibility for tight "U" bends
- For interconnecting within equipment and appliances
- Available in custom lengths or bulk packaging
- UL Recognized, File number E46112
- Acceptability of this product in an end product is determined by UL and CSA
- RoHS WEEE compliant

## USES:

International Appliance Flex Aluminum Conduit is for use in recessed light fixtures and as a wire harness within or for parts of an appliance or similar applications.

## SPECIFICATIONS:

Trade Size And Catalog Number	Acceptable Internal Diameter		Acceptable External Diameter		Bending Radius in Inches	Approx. Weight of 100 Ft.	Feet Per Standard Coil
	Min.	Max.	Min.	Max.			
AFA-5/16	0.297	0.327	0.450	0.480	1	3	250
AFA-3/8	0.360	0.390	0.530	0.560	3/4	4	250
AFA-7/16	0.422	0.452	0.575	0.605	13/16	5	250
AFA-1/2	0.485	0.515	0.640	0.670	1-1/4	5.5	250
AFA-9/16	0.547	0.575	0.705	0.735	1-1/2	6	250
AFA-5/8	0.610	0.640	0.765	0.795	1-5/8	7	250
AFA-3/4	0.735	0.765	0.895	0.925	1-3/4	7.5	250

\*Standard length tolerance on packaging +/- 2%



## INTERNATIONAL METAL HOSE COMPANY

QUALITY MATERIALS • QUALITY MANUFACTURING  
QUALITY PERFORMANCE

520 Goodrich Road – Bellevue, OH 44811-0149 – Phone: 419.483.7690  
Fax: 419.483.8225 – Toll Free: 800.458.6855 – [www.metalhose.com](http://www.metalhose.com)

